



INDUSTRIAS TECHNOFLEX SA

<http://www.technoflex.es/>

Plancha vibradora reversible con accionamiento hidráulico

Reversible compactor plate with hydraulic control

Plaque vibrante réversible avec actionnement hydraulique

Compactadora reversível com controle hidráulico

MAMUT 40-G / MAMUT 40-D



Manual de Instrucciones / Lista de Recambios

Instruction Manual / Spare Parts

Manuel d'Instructions / Liste de Pièces de Rechange

Manual de instruções / Lista de reposições

MAQUINARIA PARA LA CONSTRUCCIÓN Y OBRAS PÚBLICAS
BUILDING AND PUBLIC WORKS MACHINERY
MACHINERIE POUR LA CONSTRUCTION ET LES TRAVAUX PUBLICS
MAQUINARIA PARA A CONSTRUÇÃO E OBRAS PÚBLICAS

1B OPERATION

1.3 Technical Data

MODEL	MAMUT 40-G	MAMUT 40-D
Code	141716R013	141717R013
Control forward-reverse	Hydraulic	Hydraulic
Engine	Honda GX270	KAMA 178 F
Power (KW / HP)	6,5 / 9	4,5 / 6
Weight (Kg. / Lb)	165 / 364	173 / 381
Frequency (Hz.)	75	75
Exciter speed min ⁻¹	4600	4600
Centrifugal force (KN)	40	40
Forward speed máx. (m/min.-ft/min)	24 / 79	24 / 79
Inclination máx. (%)	30	30
Lateral inclinación máx. (°)	20°	20°
Work wide (mm / inch)	500 / 19,7	500 / 19,7
Work height (mm / inch)	900 / 35,4	900 / 35,4
Plate size (mm / inch)	500x700 19,7x27,5	500x700 19,7x27,5
Efficiency approximate (m ² /h – ft ² /h)	625 / 6727	625 / 6727
Exciter oil	Fuchs Titan Unic 10W40MC (SAE 10W40)	Fuchs Titan Unic 10W40MC (SAE 10W40)
Exciter oil quantity (l)	1,1	1,1
Control box oil forward-reverse	Fuchs Renolin MR520	Fuchs Renolin MR520
Sound Pressure Level according EN ISO 1124 (L _{pA})	95 dB (A)	95 dB (A)
Weighted Effective Acceleration according EN 1033	10 m/s ²	10 m/s ²

INDUSTRIAS TECHNOFLEX, S.A.

C/ Ctra. d'Ullastrell S/N
Apartado de correos, 43
E-08191 RUBÍ (Barcelona)-SPAIN

Tel. (+34) 93 588 53 37
Fax (+34) 93 697 37 54
e-mail: technoflex@ficsa.com
Internet: <http://www.technoflex.es>



Cód. : 4046600030 11/11



INDUSTRIAS TECHNOFLEX SA